



I - PRODUCT IDENTIFICATION AND USE				MSDS ID: 57249
PRODUCT NAME: SUMA SUPER L1				
USE: Mechanical warewashing detergent				
SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada			EMERGENCY PHONE: 1-800-668-7171	
WHMIS CLASSIFICATION: D2B E CHEMICAL FAMILY: Chlorinated Alkali			TRADE NAME / SYNONYMS: not applicable CHEMICAL NAME: not applicable	
II - HAZARDOUS INGREDIENTS				
HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Potassium hydroxide	7-13	001310-58-3	LD50 365 mg/kg	oral/rat
Sodium hypochlorite	1-5	007681-52-9	LD50 375 mg/kg	oral/rat
III - HANDLING AND DISPOSAL PROCEDURES				
PERSONAL PROTECTIVE EQUIPMENT:				
Gloves: Natural rubber, neoprene or nitrile		Eye: Safety goggles		Footwear: As required
Respiratory: Not normally required.			Other: Not normally required.	
SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. If mists are generated, use NIOSH approved mask.				
VENTILATION REQUIREMENTS: General ventilation.				
INCOMPATIBILITY (Material to Avoid): Acids, ammonia, urea, amines and soft metals.				
SPILL PROCEDURES: Wear protective clothing. Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.				
WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.				
STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container.				UN1814
IV - PHYSICAL PROPERTIES				
APPEARANCE / ODOUR: Clear pale yellow liquid - chlorine odour				
S.G. / BULK DENSITY(g/cc): not available		pH: not available		
VAPOUR PRESSURE (mmHg): not available		VAPOUR DENSITY (air=1): not available		
ODOUR THRESHOLD: 0.2-0.4 ppm chlorine		BOILING POINT: approx. 100°C		
FREEZING POINT: not available		PERCENT VOLATILE: approx. 77%		
SOLUBILITY IN WATER: soluble		EVAPORATION RATE (water=1): 1		
V - TOXICOLOGICAL PROPERTIES				
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:				
EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.				
SKIN: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.				
INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause permanent damage if not treated promptly.				
INHALATION: Corrosive. Inhalation of spray or mist may cause severe respiratory irritation.				
LD50 (calculated): 3171 mg/kg			LC50 (calculated): not applicable	

OTHER TOXIC EFFECTS: TLV-CL (potassium hydroxide) 2 mg/m3; TLV-TWA (Cl2) 0.5 ppm, STEL 1 ppm

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known

VI - FIRST AID MEASURES

EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.

SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.

INGESTION: Drink large volumes of water. Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.

INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.

VII - FIRE AND EXPLOSION DATA

FLAMMABLE: No

FLASH POINT, °C: not applicable

AUTO IGNITION TEMPERATURE, °C: N/Ap

EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.

HAZARDOUS COMBUSTION PRODUCTS: Chlorine gas and oxygen released when heated.

EXPLOSIVE SENSITIVITY TO: not applicable

VIII - REACTIVITY DATA

STABILITY: Stable [] Unstable [x]

CONDITIONS TO AVOID: Chlorine loss accelerated at high temperature and when exposed to light.

INCOMPATIBILITY (Material to Avoid) : Acids, ammonia, urea, amines and soft metals.

HAZARDOUS DECOMPOSITION PRODUCTS: Contact with acid generates heat and chlorine gas. Contact with ammonia, urea and amines produces nitrogen gas and chloramines. Contact with soft metals forms flammable hydrogen gas.

REACTIVITY: not dangerously reactive

IX - MSDS PREPARATION

SOURCES USED: RTECS, ChemInfo

PREPARED BY: JohnsonDiversey Canada, Inc.
Regulatory Department
Institutional Division
Phone (905) 829-1200

PREPARATION DATE: March 10, 2006

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.